



MODE BACK-TO-WALL TOILET

Product Image **Technical Specification**

Technical drawings include:

- Side view: Total height 798mm, tank height 178mm, seat height 404mm, floor to tank base 205mm, floor to bowl base 285mm.
- Top view: Bowl width 352mm, depth 628mm.
- Front view: Tank height 735mm, bowl height 210mm, floor to bowl base 220mm.
- Bottom view: Bowl width 215mm.

Water Rating 3.5 logo: The more stars the better. 3.5 litres average flush. 4.5 L per full / 3 L per half flush. In accordance with AS/NZS 4409. Licence No. 0008. Argent Australia.

SOFT CLOSE logo

Water Entry:	Rear water entry requires 1/2" BSP male thread extending 10mm past the finished wall			
*S-Trap Set-out options	Distance from finished wall to centre of soil pipe	Vario Bend required		Installation Notes
Recommended	140mm	5001.5P	Supplied standard with S-trap Suites	To be cut to required length on-site
Standard Adjustment Range	80-170mm	5001.5P	Supplied standard with S-trap Suites	To be cut to required length on-site
With extension bend	170-250mm	8702	Order separately with P-Trap Suite	To be cut to required length on-site - Requires installation into DWV pipe (adaptor supplied) or into a pan collar installed flush with the finished floor
Flushing Options:	4.5/3L toilets can be easily converted to 6/3L on-site where it is approved to do so; one-click conversion instructions are included inside the cistern			

Description
Mode Back-To-Wall Toilet with Soft Close Seat WELS 4 Star / 4.5/3L
KO060101S4RDB S-Trap / Rear Water Entry
KO061001S4RB P-Trap / Rear Water Entry
KO060101S4BDB S-Trap / Bottom Water Entry
KO061001S4BB P-Trap / Bottom Water Entry

Additional Information
<ul style="list-style-type: none"> Supplied standard with Soft-Close Seat S-trap or P-trap available Concealed Rear Water Entry or Bottom Water Entry option available 5 Year Ceramic Warranty (Conditions Apply)

